




## | 700 SERIES

LINEAR POSITION SENSOR



### Introduction

The 700 Series Linear Position Sensors are designed to operate reliably in extreme environments such as “down hole” oil well applications at temperatures between -40° and over 200°C and pressures of up to 35,000 psi. Containing a conductive plastic resistive element, the 700 Series has a longer operating life and resolution than traditional wire-wound units. Offered in miniature diameters for space-saving advantages, the 700 Series is also designed to meet a wide variety of interface and mounting requirements making it ideal for applications requiring accurate performance in high temperature and high pressure environments with limited space.



### SPECIFICATIONS

#### Mechanical

<b>Mechanical Travel</b>	Elect travel + 0.2 in. min
<b>Actuation Force</b>	2 oz. max
<b>Repeatability</b>	Within 0.001 inch
<b>Life</b>	5 x 10 <sup>5</sup> cycles

#### Electrical

<b>Electrical Travel</b>	1 in. min to 6 in. max
<b>Total Resistance</b>	1.23 KΩ per inch
<b>Resistance Tolerance</b>	±25%
<b>Accuracy over useable range</b>	(Ind. Lin. See Note 2) STD: ± 0.020 inch Best: ± 0.005 inch
<b>Power Rating @ 175°C</b>	0.25 Watt per inch Derated to 0.10 Watts @ 250°C
<b>Output smoothness</b>	0.1%
<b>Insulation resistance @250 VDC</b>	1000 Megohms
<b>Dielectric strength</b>	250 VRMS
<b>Operating Temperature Range</b>	-40° to +200°C
<b>Storage Temperature Range</b>	-40° to +250°C



# DIMENSIONS

Dimensions are in inches. Tolerance:  $\pm .010$





Figure 1



## General Notes

Most specifications may be altered to meet specific requirements.

Special Feature Examples:

- Vent holes for immersion in fluids.
- Mounting: Threaded bushing front/rear.
- Leads: Jacketed/Shielded cable.
- Shaft End Options: (Figure 1)

Sensata Technologies, Inc. ("Sensata") data sheets are solely intended to assist designers ("Buyers") who are developing systems that incorporate Sensata products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, evaluation and judgment in designing Buyer's systems and products. Sensata data sheets have been created using standard laboratory conditions and engineering practices. Sensata has not conducted any testing other than that specifically described in the published documentation for a particular data sheet. Sensata may make corrections, enhancements, improvements and other changes to its data sheets or components without notice.

Buyers are authorized to use Sensata data sheets with the Sensata component(s) identified in each particular data sheet. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER SENSATA INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN. SENSATA DATA SHEETS ARE PROVIDED "AS IS". SENSATA MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE DATA SHEETS OR USE OF THE DATA SHEETS, EXPRESS, IMPLIED OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. SENSATA DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, QUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO SENSATA DATA SHEETS OR USE THEREOF.

All products are sold subject to Sensata's terms and conditions of sale supplied at [www.sensata.com](http://www.sensata.com) SENSATA ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR THE DESIGN OF BUYERS' PRODUCTS. BUYER ACKNOWLEDGES AND AGREES THAT IT IS SOLELY RESPONSIBLE FOR COMPLIANCE WITH ALL LEGAL, REGULATORY AND SAFETY-RELATED REQUIREMENTS CONCERNING ITS PRODUCTS, AND ANY USE OF SENSATA COMPONENTS IN ITS APPLICATIONS, NOTWITHSTANDING ANY APPLICATIONS-RELATED INFORMATION OR SUPPORT THAT MAY BE PROVIDED BY SENSATA.

Mailing Address: Sensata Technologies, Inc., 529 Pleasant Street, Attleboro, MA 02703, USA.

## CONTACT US

### Americas

+1 (800) 350 2727  
sensors@sensata.com

### Europe, Middle East & Africa

+33 (3) 88 20 8080  
position-info.eu@sensata.com

### Asia Pacific

sales.isasia@list.sensata.com  
China +86 (21) 2306 1500  
Japan +81 (45) 277 7117  
Korea +82 (31) 601 2004  
India +91 (80) 67920890  
Rest of Asia +886 (2) 27602006  
ext 2808