



| 5TC SERIES

20 to 50 Amp, Single-Phase, Ambient Compensated

Introduction

Klixon® single-phase TC devices are the smallest, lightest, high performance aircraft circuit breakers available today. They represent the state-of-the-art protection of today's aerospace power systems. Their light weight and small size make them especially well suited for aircraft, avionics and electronic systems.

The Klixon® trademark has set the standard for aerospace circuit breakers. For a small, light weight configuration, the TC series offers the endurance and reliability required by exacting military specifications, and are available in standard current ratings from 1 through 50 amperes.



Features

- Miniature size
- Light weight
- Single-phase
- Ambient compensated
- Trip-free design
- Current rating: 20 to 50 amps
- Coordinated ratings
- High vibration resistance
- High interrupting capacity
- Options include: standard or auxiliary switch configuration, terminal barriers
- Typical use: Aircraft, avionics and electronic systems



PERFORMANCE CHARACTERISTICS

Vibrations	10G minimum, 80–500 Hz (other vibration levels available)	
Mechanical Shock	50G	
Acceleration	10G	
Weight	Standard device: 53 grams (no hardware), 58 grams (hardware) Auxiliary device: 55 grams (no hardware), 59 grams (hardware)	
Interrupt Current	20–50 amps: 4000 amps at 28 VDC 20–50 amps: 2000 amps at 115 VAC, 400 Hz	
Endurance	2,500 cycles: 115 VAC, 400 Hz inductive 2,500 cycles: 28 VDC inductive	2,500 cycles: 28 VDC resistive 5,000 cycles: Mechanical, no load

QUALIFICATIONS

ASNE	ASNE0732-005 (our 5TC65 auxiliary device)
NSA	NSA93121 (our 5TC50 standard device)

CALIBRATION CHART

For a Standard Device

Temp.	Minimum Trip	Ultimate Trip	Trip Time (in seconds)		
			200%	500%	1000%
23°C	110%	145%	2–18	0.15–2.5	0.045–0.6
-54°C	110%	165%	70 seconds max.	0.15–2.5	0.045–0.6
70°C	105%	145%	1.5 seconds min.	0.15–2.5	0.045–0.6
125°C	90%	145%	1.5 seconds min.	0.15–2.5	0.045–0.6

The most typical device is 3–35 amps. For others, please contact us.

VOLTAGE DROP

Amp Rating	Max. Voltage Drop*
20	0.15
25	0.15
35	0.15
50	0.15

*Maximum voltage drop at nominal rated current.

Sensata Technologies, Inc. ("Sensata") data sheets are solely intended to assist designers ("Buyers") who are developing systems that incorporate Sensata products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, evaluation and judgment in designing Buyer's systems and products. Sensata data sheets have been created using standard laboratory conditions and engineering practices. Sensata has not conducted any testing other than that specifically described in the published documentation for a particular data sheet. Sensata may make corrections, enhancements, improvements and other changes to its data sheets or components without notice.

Buyers are authorized to use Sensata data sheets with the Sensata component(s) identified in each particular data sheet. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER SENSATA INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN. SENSATA DATA SHEETS ARE PROVIDED "AS IS". SENSATA MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE DATA SHEETS OR USE OF THE DATA SHEETS, EXPRESS, IMPLIED OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. SENSATA DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, QUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO SENSATA DATA SHEETS OR USE THEREOF.

All products are sold subject to Sensata's terms and conditions of sale supplied at www.sensata.com. SENSATA ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR THE DESIGN OF BUYERS' PRODUCTS. BUYER ACKNOWLEDGES AND AGREES THAT IT IS SOLELY RESPONSIBLE FOR COMPLIANCE WITH ALL LEGAL, REGULATORY AND SAFETY-RELATED REQUIREMENTS CONCERNING ITS PRODUCTS, AND ANY USE OF SENSATA COMPONENTS IN ITS APPLICATIONS, NOTWITHSTANDING ANY APPLICATIONS-RELATED INFORMATION OR SUPPORT THAT MAY BE PROVIDED BY SENSATA.

Mailing Address: Sensata Technologies, Inc., 529 Pleasant Street, Attleboro, MA 02703, USA.

CONTACT US

Americas
+1 (508)-236-3287
klixon@sensata.com

AUTHORIZED DISTRIBUTORS
Flame Enterprises
Bob Correa, Director of Product Management
+1 (240) 236-9802
bcorrea@flamecorp.com
info@flamecorp.com | Web
Tel: 1-800-854-2255 or 1-818-700-2905
Fax: 1-818-407-5080

Peerless Electronics
Steve Gunther, National Sales Manager

+1 (516) 594-3509
sgunther@peerlesselectronics.com
nysales@peerlesselectronics.com | Web
Tel: 1-800-285-2121
Fax: 1-800-222-8096

Europe, Middle East & Africa
Flame Enterprises
Bob Correa, Director of Product Management
+1 (240) 236-9802
bcorrea@flamecorp.com
info@flamecorp.com | Web
Tel: 1-800-854-2255 or 1-818-700-2905
Fax: 1-818-407-5080