


CYLINDRICAL HOUSED LINEAR VCA WITH AN INTEGRATED SENSOR

Introduction

The “Linear Voice Coil Actuator (VCA) with Integrated Position Sensor” is a housed VCA with an integrated Hall effect sensor. This convenient design enables users to run the actuator in a closed loop, allowing them to directly control the velocity, position, acceleration and/or oscillation of the shaft. In applications where high speed, high reliability, extreme accuracy, and superior performance are vital, this actuator is the perfect match.

BEI Kimco’s Voice Coil Actuator (VCA) Developer’s Kit pairs several “Cylindrical Housed Linear Voice Coil Actuators (VCA) including an Integrated Sensor ” with their corresponding controller, software and cables, allowing customers to quickly develop an actuation system and demonstrate a working design concept. For more information, [click here](#).



Features

- Easiest VCA to integrate into customer applications
- Resolution of up to 10 microns
- Absolute analog output
- Compatible with several DC servo drive controllers
- Life tested in excess of 500 million cycles

CYLINDRICAL HOUSED LINEAR VCA WITH AN INTEGRATED SENSOR CONFIGURATIONS

Part Number	Peak Force (N / lb)	Total Stroke (mm / in)	Continuous Stall Force (N / lb)	Actuator Constant (N/√watt / lb/√watt)	Outside Diameter/ Width (mm / in)	Length at Mid-stroke (mm / in)	Resolution
LAS13-18-000A-P01-3E	15.57 / 3.5	6.36 / 0.25	5.07 / 1.14	2.36 / 0.53	31.62 / 1.25	45.72 / 1.8	10
LAS13-18-000A-P01-3S	15.57 / 3.5	6.36 / 0.25	5.07 / 1.14	2.36 / 0.53	31.62 / 1.25	45.72 / 1.8	10
LAS13-56-000A-P01-6E	97.36 / 21.9	12.8 / 0.5	23.1 / 5.19	7.63 / 1.72	33 / 1.3	142.2 / 5.6	20
LAS16-23-000A-P01-4E	89 / 20	6.08 / 0.24	17 / 3.82	5.83 / 1.31	40 / 1.58	58.42 / 2.3	10
LAS16-23-000A-P01-4S	89 / 20	6.08 / 0.24	17 / 3.82	5.83 / 1.31	40 / 1.58	58.42 / 2.3	10
LAS22-42-000A-P01-6E	106.7 / 60	25.4 / 1	23.2 / 5.2	5.57 / 1.25	55.9 / 2.2	106.7 / 4.2	40
LAS22-42-000A-P01-6I	106.7 / 60	25.4 / 1	23.2 / 5.2	5.57 / 1.25	55.9 / 2.2	106.7 / 4.2	40
LAS28-53-000A-P01-12E	266.9 / 60	25 / 0.98	60.1 / 13.5	13.09 / 2.94	70 / 2.76	132.7 / 5.22	40
LAS28-53-000A-P01-12I	266.9 / 60	25 / 0.98	60.1 / 13.5	13.09 / 2.94	70 / 2.76	132.7 / 5.22	40
LAS28-53-000A-P01-12S	266.9 / 60	25 / 0.98	60.1 / 13.5	13.09 / 2.94	70 / 2.76	132.7 / 5.22	40
LAS43-88-000A-P01-10E	1512.4 / 30	31.74 / 1.25	285.5 / 64.2	38.3 / 8.61	109.22 / 4.3	223.52 / 8.8	50
LAS43-88-000A-P01-10I	1512.4 / 340	31.74 / 1.25	285.5 / 64.2	38.3 / 8.61	109.22 / 4.3	223.52 / 8.8	50

Datasheets provided by Sensata Technologies, Inc., its subsidiaries and/or affiliates ("Sensata") are solely intended to assist third parties ("Buyers") who are developing systems that incorporate Sensata products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, valuation, and judgment in designing Buyer's systems and products. Sensata datasheets have been created using standard laboratory conditions and engineering practices. Sensata has not conducted any testing other than that specifically described in the published documentation for a particular datasheet. Sensata may make corrections, enhancements, improvements, and other changes to its datasheets or components without notice.

Buyers are authorized to use Sensata datasheets with the Sensata component(s) identified in each particular datasheet. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER SENSATA INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN. SENSATA DATASHEETS ARE PROVIDED "AS IS". SENSATA MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE DATASHEETS OR USE OF THE DATASHEETS, EXPRESS, IMPLIED, OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. SENSATA DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, QUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO SENSATA DATASHEETS OR USE THEREOF.

All products are sold subject to Sensata's terms and conditions of sale supplied at www.sensata.com. SENSATA ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR THE DESIGN OF BUYERS' PRODUCTS. BUYER ACKNOWLEDGES AND AGREES THAT IT IS SOLELY RESPONSIBLE FOR COMPLIANCE WITH ALL LEGAL, REGULATORY, AND SAFETY-RELATED REQUIREMENTS CONCERNING ITS PRODUCTS, AND ANY USE OF SENSATA COMPONENTS IN ITS APPLICATIONS, NOTWITHSTANDING ANY APPLICATIONS- RELATED INFORMATION OR SUPPORT THAT MAY BE PROVIDED BY SENSATA.

Mailing Address: Sensata Technologies, Inc., 529 Pleasant Street, Attleboro, MA 02703, USA

CONTACT US

Americas

+1 (760) 597 7042

sales.beikimco@sensata.com

Europe, Middle East & Africa

+1 (760) 597 7042

motors-info.eu@sensata.com

Asia Pacific

sales.isasia@list.sensata.com

China +86 (21) 2306 1500

Japan +81 (45) 277 7117

Korea +82 (31) 601 2004

India +91 (80) 67920890

Rest of Asia +886 (2) 27602006
ext 280