



# | MOTOR STARTER-PROTECTOR COMBO (MSC) REFRIGERATION PACKAGE

COMPACT, RELIABLE, LOW POWER CONSUMPTION

## Introduction

The Klixon® MSC refrigeration pack-age is a compact motor starter and motor protector package that dissipates less than 2 watts under typical operating conditions.



**Standard**



**1-Piece (RSCR)**



**2-Piece (RSCR)**



**Terminal Board**

## Overview

The MSC by Sensata Technologies serves as a combination control that:

- Uses compact metal can motor protector and solid state PTC motor starter
- Includes Internal Back-up Protection System for the PTC motor starter
- Available for RSCR applications (Contact Sensata for alternate configurations)
- Plugs directly onto compressor terminal pins
- Dissipates less than 2 watts under typical operating conditions

## Features

- Applicable to fractional horsepower compressors used in residential refrigerators and freezers, and similar refrigeration applications
- Utilizes ceramic PTC (Positive Temperature Coefficient) thermistor element to energize / de-energize motor start windings
- Available for 120 and 220 volt applications
- Configurations available to suit most residential applications
- Less costly to install than discrete motor starter and protector components

## SPECIFICATIONS

### General

<b>Temperature Limits</b>	Ambient Air: 0°C to 70°C
<b>Electrical Requirements</b>	120 or 240 VAC nominal voltage (50 or 60 Hz)

### Motor Starter

<b>Room Temperature Resistance</b>	3.9Ω to 47Ω ratings available ±25% resistance tolerance
<b>Switch Time</b>	0.1 – 1.4s at 120 or 240 VAC
<b>Reliability</b>	500,000 cycles at maximum rated conditions of voltage and current

## Motor Protector

<b>Device Actuation Temperatures</b>	Open Temperature: 100°C to 160°C ± 5°C Close Temperature: 55°C to 70°C ± 9°C Temperature Differential: 60°C typical
<b>Rated Hot Locked Rotor Current</b>	120 VAC: 18.0 A maximum 240 VAC: 10.0 A maximum 60% power factor
<b>Ultimate Trip Current</b>	0.5 – 5.5 A @ 71°C
<b>Endurance<sup>1</sup></b>	Minimum of 15,000 cycles at maximum rated current at 120 and 240 volts, as predicted by Weibull analysis of the test data. This protection must be verified in the end application.

<sup>1</sup> A failure is defined as an open circuit or permanently closed circuit, rapid cycle (>3X normal rate), or by a change in the open or close temperature of more than 10% from the original values.



## CONFIGURATIONS

### MSC Standard

Multiple quick connect (QC) terminal configurations available; designed to be used with secondary compressor relay cover

### MSC One-Piece Connector

3.2 mm x 0.5 mm terminals for use with standard insulated connector

### MSC Two-Piece Connector

1/4" and/or 3/16" QC terminal configurations for use with standard insulated connectors


### MSC Terminal Board

Multiple QC and screw terminal configurations available; designed to be used with secondary compressor relay cover



## APPLICATION NOTES

1. The surface and terminals of the MSC device can reach high temperatures under typical running conditions. Any material in contact with the MSC and its terminals, including wire and quick-connect receptacle plastic insulation, should have a minimum temperature rating (UL RTI) of 105°C. Adequate spacing should be provided to insulate lower-rated materials from this heat source.
2. The MSC device should be protected from potential sources of liquid, such as the evaporator tray and water connections.
3. Certain materials, such as chlorine (Cl) containing gases, can degrade the characteristics of the MSC device. The MSC device should not be exposed to sulphur (S) or chlorine (Cl) containing gases, and must be kept away from materials that can generate them. In particular, avoid the use of polyvinyl chloride (PVC) insulation in contact with the MSC terminals.
4. The MSC device should not be exposed to hydrocarbon based materials, as they can cause a degradation in the PTC characteristics.
5. The final device configuration selection will determine the necessity for a secondary compressor relay cover and or supplemental retention requirements.
6. The installation force applied to the MSC device must be in parallel with the compressor feedthrough pins and must not exceed 20 kgf (44 lbs).




### Glossary


<b>R<sub>0</sub></b>	Measured resistance value at 25°C at maximum of 2.0 volts
<b>Switch Time (t<sub>s</sub>)</b>	Time required for the inrush current to decrease to 1/2 of its initial value
<b>Switch (Curie) Temp. (T<sub>s</sub>)</b>	Temperature at which the PTC resistance value is 2X the 25C value (R <sub>0</sub> )
<b>Reset Time</b>	Time required for the PTC resistance to return to 2X the initial value (2R <sub>0</sub> )
<b>V<sub>max</sub></b>	Maximum operating voltage that may be applied across the PTC
<b>V<sub>r</sub></b>	Nominal rated supplied voltage: 120 or 240 VAC (<V <sub>max</sub> )
<b>I<sub>ss</sub></b>	Steady state current remaining at maximum operating voltage
<b>I<sub>max</sub></b>	Maximum operating (inrush) current



MSC STD




RS\*R




CS\*R

MSC 1-PC  
MSC 2-PC



RSCR




RSIR

- ↑ Quick-connect terminal
- ↑ Pin connector
- ↑ Run Capacitor connector (outputs)



# ORDERING OPTIONS

Example : MSC 1 4 A 13 A 5 - 01



## AGENCY APPROVALS & CERTIFICATIONS



<b>UL / C-UL</b>	File# SA3745
<b>KEMA / ENEC</b>	Certification # 2014531.01 IEC/EN 60730-2-4: 2007 IEC/EN 60730-2-10: 2007 IEC/EN 60079-15: 2005 IEC/EN 60335-1: 2001, clause 30.2.3
<b>CQC</b>	Certification 08002025660
	RoHS Compliant

Sensata Technologies, Inc. ("Sensata") data sheets are solely intended to assist designers ("Buyers") who are developing systems that incorporate Sensata products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, evaluation and judgment in designing Buyer's systems and products. Sensata data sheets have been created using standard laboratory conditions and engineering practices. Sensata has not conducted any testing other than that specifically described in the published documentation for a particular data sheet. Sensata may make corrections, enhancements, improvements and other changes to its data sheets or components without notice.

Buyers are authorized to use Sensata data sheets with the Sensata component(s) identified in each particular data sheet. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER SENSATA INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN. SENSATA DATA SHEETS ARE PROVIDED "AS IS". SENSATA MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE DATA SHEETS OR USE OF THE DATA SHEETS, EXPRESS, IMPLIED OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. SENSATA DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, QUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO SENSATA DATA SHEETS OR USE THEREOF.

All products are sold subject to Sensata's terms and conditions of sale supplied at [www.sensata.com](http://www.sensata.com) SENSATA ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR THE DESIGN OF BUYERS' PRODUCTS. BUYER ACKNOWLEDGES AND AGREES THAT IT IS SOLELY RESPONSIBLE FOR COMPLIANCE WITH ALL LEGAL, REGULATORY AND SAFETY-RELATED REQUIREMENTS CONCERNING ITS PRODUCTS, AND ANY USE OF SENSATA COMPONENTS IN ITS APPLICATIONS, NOTWITHSTANDING ANY APPLICATIONS-RELATED INFORMATION OR SUPPORT THAT MAY BE PROVIDED BY SENSATA.

Mailing Address: Sensata Technologies, Inc., 529 Pleasant Street, Attleboro, MA 02703, USA.

### CONTACT US

**Americas**  
+1 (508) 236-2551  
electrical-protection-sales@sensata.com

**Europe, Middle East & Africa**  
+3 174 357 8156  
info-sse@list.sensata.com

**Asia Pacific**  
EP\_Asia\_Public@list.sensata.com  
China +86 (21)2306 1651  
India +91 (40)4033 9611  
Japan +81 (45)277 7104  
Korea +82 (53) 644 9685  
Rest of Asia +65(6478)6860